



## SIC-20EA473-5D

4 IN 1 AHD 2.0MP VARIFOCAL METAL DOME CAMERA SONY SENSOR



### Product Highlights

- 1/3" 2 MP Sony Sensor
- 1920 (H) x 1080 (V) Effective Pixels
- IR Distance of 30 m
- 2.8 - 12 mm Varifocal lens
- Auto Day/Night Mode
- Auto Gain Control (AGC)
- 2D DNR (Digital Noise Reduction)
- Auto White Balance (AWB)
- Smart IR
- Wide temperature range of -10° C to 50° C
- IP 66

## Specifications

<b>Model Number</b>	<b>SIC-20EA473-5D</b>
<b>Camera</b>	
Image Sensor	1/3" Sony Sensor
Effective Pixels	1920 (H) × 1080 (V)
Resolution	2 Mega Pixel
Frame Rate	25 fps
Scanning System	2 : 1 Interlace
Electronic Shutter Speed	1/50 - 1/ 100000 Seconds
Minimum Illumination	0.1 Lux @ (F1.2,AGC ON),0 Lux with IR
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	52 dB
<b>IR</b>	
No. of LEDs	36
IR Distance	30m
IR On/Off Control	Auto
<b>Lens</b>	
Lens Type	Varifocal Lens
Mount Type	Board Lens
Focal Length	2.8mm-12mm
Max Aperture	F1.4 3.6
Angle of View	98.5° - 23.5°
<b>Functions</b>	
Day/Night	Auto
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D DNR
White Balance	Auto
Smart IR	Auto
<b>Electrical</b>	
Power Supply	12 V DC ± 10 % with IR ON
Power Consumption	Max. 1.5 W (Max. 4.5 W with IR cut filter on)
<b>Construction</b>	
Casing	Dome
Dimensions	131 × 93 × 131 mm
Gross Weight	0.400 kg
Material	Metal
Net Weight	0.450 kg
<b>Enviromental</b>	
Operating Temperature	-10°C - 50°C and 90% humidity or less than that
Storage Temperature	Below 40°C
Ingress Protection & Vandal Proof	IP 66
<b>Certifications</b>	<b>CE, FCC, UL &amp; RoHS</b>

## Dimensions

